

NEED TO ELIMINATE DOWNTIME
& REDUCE MAINTENANCE COSTS ?



FEATURES

- TEFC Stainless Steel Supply Pumps Sized to Fit Any Press
- Twin Bag Filtration – Removable for Tank Cleaning
- Corrosion-Resistant Industrial Fiberglass Skid Construction
- Chemical Resistant Polypropylene Piping Network
- Large Capacity Tank for Holding Return Solution for Maintenance
- Low-Level Control Prevents Pump from Running Dry
- 2-Year Warranty on Materials & Workmanship



*We can't prevent system failure ... but ... we can change
what happens to your production schedule
when failures do occur with the ...*

C-600

CIRCULATOR SYSTEM



12455 SW 7th Place
Fort Lauderdale, Florida 33325 USA
T 954.236.4507
F 954.236.5174
E info@sincal.net

For more information on our products and services, visit us on the World Wide Web www.sincal.net or contact us directly.

C-600 Options

- **Back-Up Supply Pump**
Including all Necessary Piping and Pre-Wired to a Selector Switch.
- **1/2" or 1" Power Return Pump**
Includes Filter/Regulator, Quick Disconnect Fittings and Hoses.
- **Press Side Accumulator Tank**
Includes Pre-Filters and Controls for Diaphragm Pump Operation.
- **Stainless Steel Plate Heat Exchanger**
With Manual Valve Modulation including all the Necessary Fittings and Stainless Steel (Field Installed)
- **Chilling System**
Custom sized for specific pressroom requirements.
- **Conductivity Meter Assembly**
Includes Probe, Mounted in Fiberglass Box includes Fittings & Power Cord (120V/60).
- **Conductivity/pH Meter**
Includes Probe, Mounted in Fiberglass Box includes Fittings & Power Cord (120V/60)
- **Remote Digital L.E.D. Meter**
For Monitoring Conductivity or pH up to 2,000' from the Main Unit.
- **Mechanical Float Valve**
For Automatic Filling.
- **Spare Parts Package**

Specifications & Dimensions

General	
---------	--

Model:	C-600 Circulator
Frame:	30" W x 54" L x 40" H

Service Requirements & Connections	
------------------------------------	--

Electrical:	208-230V/60Hz/1 PH
	220-240V/50Hz/1 PH
	3/4 HP - 6.9 FLA
	1 HP - 8.0 FLA
	1 1/2 HP - 10.0 FLA
	2 HP - 12.0 FLA
	Shipped with a 10' power cord

Operational	
-------------	--

Supply Pump:	TEFC stainless steel close-coupled sized to fit any press.
Filtration:	100 micron twin bag filters.
Tank:	90 gallon capacity. Normal operating level is 25 gallons.