NP-1 Reconditioned Strapping Machine

If reliability and ROI is what your searching for, look no further than Dynaric's Pre-Owned and Reconditioned NP-1 Strapping Machine. The NP-1 comes with a long and proven record of superior performance in its proud history. Being the first strapping machine of its kind offered to the industry from Dynaric, this unit has been in great demand for the past 15 years. The NP-1 comes backed with the Dynaric name and outstanding customer service program.

The NP-1 offers a cycle speed of 1.7 seconds per cycle and will strap 34 bundles per minute in a single strap application and 17 in a parallel strapping application. Providing superior output and outstanding reliability, the NP-1 is extremely cost effective to own and operate due its low maintenance costs. The NP-1 can be easily intergrated into today's automated mailrooms by incorporating optional electrical interlock connectors.

The NP-1 can inprove the production of many other different types of industries such as: high volume distribution centers, commercial printers, cut sheet paper companies and packaged food compaines.



Quick Change Dispenser

Easy loading and unloading of strap coils

Bundle Conditioning System

Squares up bundle prior to strapping for a more uniform bundle

Warning Light System

Visual warning notification

Compression Unit

Automatically adapts to the contour of your bundle

Strap Feeding

Two smooth steel rollers plus two auxiliary rollers

Table top Conveyers

Ingoing - 3 flat rubber belts Outgoing - 2 flat rubber belts

Soft Clamp Compression

Shapes itself to bundle contour for more uniform compression

Low Noise Factor

Limits irritating noise in the mailroom

Table Height Adjustment

Adapts to various height conveyor systems


Bundle Tension


Accomplished in a two stage process

Dynaric, Inc.

5740 Bayside Road, Virginia Beach, VA 23455 Toll free: 800-526-0827 Fax: 757-363-8016 E-mail: order@dynaric.com Web Site: www.dynaric.com

NP-1 Reconditioned Strapping Machine





Front View

SPECIFICATIONS

Overall Width:	28" (720mm)
Overall Length:	64" (1618mm)
Overall Height:	65" (1650mm)
Weight:	1100 lbs. (500kg)
Speed:	34 Bundles / min., single strap 17 Bundles / min., double strap
Strap Size:	1/4" strapping
Air Requirements:	85 - 100 psi
Table Height:	34.5" (875mm)

Conveyor Speed:	120" per minute
Sealing Method:	Heat Sealed
Seal Joint:	Weld Length 1"
Operation:	Electro-pneumatic
Power Supply:	220V, 3 phase, 60 Hz. 480V, 3 phase, 60 Hz.
Max Bundle Size:	23.6" W x 19.6" H
Min. Bundle Size:	2" W x .5" H

