

# SYSTEM # 4



## 2420MTB-II SEALER/TD-18-8M TUNNEL SYSTEM



### System Features

- 24" x 20" seal area
- Self-adjusting seal pads
- Fully welded heavy steel frame
- 15-18 packages per minute
- Automatic dual magnets
- Variable speed soft start conveyor
- Stainless steel film hold downs
- Film tension brake
- Easy quick change Mono seal wire
- Fully welded seal head
- Stainless steel product loading tray
- 18" wide 8" tall 36" long tunnel chamber
- 3 Adjustable air dampers
- Dual high velocity/volume blower
- Heat ducted to all sides, top and bottom
- Automatic cool down circuit
- Digital P.I.D. temperature control
- Variable speed 0-120 fpm conveyor
- No maintenance mesh belt
- Durable electro-static powder finish
- 8000 watts of available heat
- ONE YEAR WARRANTY (including seal wire)

MODEL	MACHINE SIZE L x W x H	SHIPPING SIZE/ WEIGHT	POWER REQUIRED	SEAL AREA TUNNEL AREA	PACKAGES PER MINUTE	MAXIMUM PRODUCT SIZE
2420 MTB-II L-SEALER	60" x 39" x 36"	73" x 52" x 59" 576 LBS	220 1ph VOLTS 15 AMPS	20" x 16" L x W	15 -18	23" x 19" L x W
TD-18-8-M TUNNEL	44" x 30" x 52"	73" x 52" x 59" 475 LBS	220VOLTS 1PH 40 AMPS	18" x 8" x 36" W x H x L	30 - 40	17" x 7" W x H