

SYSTEM # 5

BESELER

2420MTB-II SEALER/TD-20-12 TUNNEL SYSTEM



System Features

- 24" x 20" seal area
- Self-adjusting seal pads
- Fully welded heavy steel frame
- 15 - 18 packages per minute
- Automatic dual magnets
- Variable speed soft start conveyor
- Stainless steel film hold downs
- Film tension brake
- Easy quick change Mono seal wire
- Fully welded seal head
- Stainless steel product loading tray
- 20" wide 12" tall 54" long tunnel chamber
- Adjustable air dampers
- Adjustable high velocity/volume blower
- Heat ducted to all sides, top and bottom
- Automatic cool down circuit
- Digital P.I.D. temperature controller
- Variable speed 0-120 fpm conveyor
- No maintenance mesh belt
- Durable electro-static powder finish
- 12,000 watts of available heat
- ONE YEAR WARRANTY (Including sealwire)

MODEL	MACHINE SIZE L x W x H	SHIPPING SIZE/ WEIGHT	POWER REQUIRED	SEAL AREA TUNNEL AREA	PACKAGES PER MINUTE	MAXIMUM PRODUCT SIZE
2420 MTB-II L-SEALER	60" x 39" x 36"	73" x 52" x 59" 576 LBS	220 1ph VOLTS 15 AMPS	20" x 16" L x W	15 - 18	23" x 19" L x W
TD-20-12 1 ph TUNNEL	79" x 34" x 45"	87" x 52" x 65" 690 LBS	220VOLTS 1PH 60 AMPS	20" x 12" x 72" W x H x L	60 - 75	19" x 11" W x H